

2
B

G
T
B



General	
Frequency range	VHF: 136-174MHz UHF: 350-370MHz; 400-420MHz; 450-470MHz
Channel Spacing	12.5kHz / 25kHz
Power supply	7.5V
Operating temperature	-25~55
Number of Channels	16 (15+5)
Battery (Standard)	1800mAh (Li-ion Battery)
Dimensions (W X H X D)	105x62x35mm
Weight	233g
Receiver	
Sensitivity (12 dB SINAD)EIA	0.15uV / 0.18uV
Intermodulation EIA	65dB
Adjacent channel selectivity	70dB / 60dB
Spurious rejection	≥70dB
Rated Audio	1W
Audio distortion @ rated audio	≤5%
Audio response (300-3000Hz)	≥70dB
Transmitter	
Power output	UHF : 4W/1W; VHF : 5W/1W
Modulation Type	16kΦF3E / 8kΦF3E
Modulation limiting	≤5KHz / ±2.5KHz
FM Hum and noise	-45dB / -40dB
Conducted/Radiated emission	-36dBm
Adjacent channel power	-70dB / -60dB
Audio distortion	≤5%

NOTE: The specifications may be subject to change without notice due to advancement in technology, for more detailed information, please contact BluFi Wireless USA.

Compatible Accessories



Charger Adapter



Desktop Charger



Ear-piece Mic



Antenna(UHF)



Li Battery



Belt Clip



41 Odell Schoo Road, Suite I,
Concord, NC 28027
(704) 412-7555
www.techsources.us
sales@techsources.us